Youth Health & Development Organization موسسه خدمات صحی و انکشافی برای جوانان (RFQ)Request for Quotation درخواست نرخ نامهٔ

Date: From 29-01-2023 to 11-02-2023

تاريخ: از 29-01-2023 الى 11-02-2023

English

Introduction:

YHDO is a non-governmental, non-political, not for profit and independent organization.

Requirement:

YHDO wants to purchase the Attached List of Medical supplies for its project and is kindly informing the interested suppliers to submit us their quotations, applications, and a copy of their business license before the closing date.

Conditions:

- 1-The respected suppliers have to provide quotations in AFN according to the specification of the official quotation form of YHDO.
- 2-The selected vendors should have enough space and stock, to stock their items until they are completely packed and then make they Have to deliver them to YHDO's required place.
- 3-The suppliers have to provide the contracted items to YHDO at the specified time and there no delay is accepted in delivery.
- 4-The provider companies should be legally registered and affiliated with Government and have registration certificates.
- 5-The supplier must mention their full ID at the back of envelop in which they submit their RFQ and quotations.
- 7- An amount of 2% tax will be deducted from the total amount of the purchases from Suppliers who have a Business License. this tax within 10 days will be paid to the government in the name of the company.
- 8- An amount of 7% tax will be deducted from the total amount of the purchases from Suppliers who do have not a Business License. this tax within 10 days will be paid to the government in the name of the company.
- 9- The Payment will be made through a bank to the supplier after the successful delivery and completion of the documentation.

10-The delivery of Medical Equipments to YHDO Stock in Kabul province is the responsibility of the supplier.

Dari

مقدمه

مؤسسه صحي و آنگشآقي جوآنان يک سازمان غير دوآتي، غير سياسي، غير انتفاعي و مستقل است. كه اساسا در بخش هاي صحي و تحقيق و انكشاف جامعه فعاليت مينمايد.

مقرره:

دفتر (YHDO) متقاضای خریداری لوازم طبی برای پروژه خود بوده و با مهربانی به اطلاع تامین کنندگان علاقمند میرساند که آنها قبل از تاریخ ختم نقل قول های، برنامه های کاربردی و یک کاپی مجوز کار خود را ارسال کنند.

شرايط:

۱ تهیه کننده گان محترم باید نرخ نامه ها را مطابق مشخصات نرخ نامه های دفتر (YHDO) به افغانی تهیه نمایند.

 ۲ فروشندگان منتخب باید جای کافی برای سهام خود داشته باشند تا اجناس خود را تا زمانی که به طور کامل بسته بندی شده اند ذخیره نموده، و سپس آنها را باید به محل مورد مورد ضرورت YHDO

٣. فروشنده محترم مكلف است تا مواددر خواست شده را بدون
 تأخير تهيه نمايد. موسسه هيچنوع تأخير را پذيرفته نميتواند.

۴ شرکت های تهیه کننده باید به طور قانونی ثبت شده دولت باشند و گو اهینامه ثبت نام داشته باشند.

۵ تهیه کننده گان باید در عقب پاکت جای که RFQ را ارسال میکنند ID مکمل خوده را تذکر دهند.

مبلغ 2٪ مالیات از کل مبلغ خرید از تامین کنندگان که جواز شرکتی
 دارند کسر می شود. این مالیات ظرف مدت 10 روز به دولت به نام
 شرکت پرداخت می شود.

٧.مبلغ 7٪ مالیات از کل مبلغ خرید از تامین کنندگان که جواز شرکت ندارند کسر می شود. این مالیات ظرف مدت 10 روز به دولت به نام شرکت پرداخت می شود.

۸. پرداخت پول بعد از انتفال موفقانه لوازم طبی و تکمیل شدن اسناد
 به حساب بانکی قرادادی ترانسفر میگیرد.

۱۰ اتتقال لوازم طبی به گدام مرکزی و لایت کابل دفتر YHDO به
 دوش قر ار داد گیر بنده میباشد.

- 11- Medical Equipments of best quality and from best companies will be appreciated and considered.
- 12- The shortlisted suppliers will provide samples of requested Medical Equipments.
- 13- The quantity of items may be changed based on the available fund for the total Medical Equipments..

Terms of Selections:

- 1-Selections of the vendors who are considered as the winners are going to be done after the collection and analysis of all the quotations.
- 2-Selection of the vendors will be based on having the best quality, lowest price, and date of delivery from reliable companies.
- 3-The best vendor will be selected by the committee members and the YHDO management team.

The closing date for Collecting the Quotations and Applications is :

11-Feb-22

Send your quotations at:

Email:(applications.yhdo@gmail.com)

Address: (House number 04, St# 2, Karta-e-se, Behind of Kateb University, Kabul Afghanistan)

Supplier:

I Certify having read, understood, and accepted the above-mentioned terms and conditions for the RFQ and certified to supply the contracted items accordingly.

Name of the Business:

Location:

Date:

Signature and stamp

۱۰ به اجناس که از کمپنی های معتبر باشد و کیفیت خوب داشته باشد
 حق اولیت داده میشود.

۱۲. فروشندگان شارت لست شده باید نمونه های اجناس طبی را ارایه نمانند

١٣. تعداد ومقدار اجناس به مطابق بوديجه قابل تغير ميياشد.

مقررات انتخاب:

۱. انتخاب فروشندگان که به عنوان برنده در نظر گرفته می شوند پس
 از جمع آوری و تجزیه و تحلیل تمام نرخ نامه ها انجام می شود.

۲ انتخاب فروشندگان بر اساس داشتن کیفیت اعلی ، قیمت نازل و تحویل به موقع از شرکت های قابل اعتماد انتخاب میگردند.

۳ بهترین فروشنده توسط اعضای کمیته مدیریت YHDO انتخاب میشوند.

تاریخ ختم جمع اوری نرخ نامه ها و درخواست است:

11/.7/7.77

ارسال نرخ نامه ها در:

(applications.yhdo@gmail.com) ایمیل:

ادرس: (خانه نمبر ۰۴ کوچه نمبر ۲ کارته سه عقب پوهنتون کاتب, کابل افغانستان)

تهیه کننده:

من با اطمینان از خواندن، درگ و قبول شرایط و ضوابط مذکور در مورد RFQ و تأبید نمودن آن به منظور تأمین اقلام قرار دادی، اطمینان حاصل کنید.

نام تجارت:

موقعيت:

تاريخ:

امضا و تایه

تهیه کننده: Prepared By:

Position Logistic Coordinator

Signature:

منظور شده: Approved by:منظور شده

Position: Executive Director

YHSignasare

Y.H.D.O **Outh Health & Development Organization

مؤسسه صحي و انكشافي جوانان Youth Health & Development Organization (YHDO)

SN Equipment Name Specification Quantity Unite Price Remarks 1 Medical Oxygen Medical Oxygen Gas Cylinder 50 Litter with regulator, Cylinder Price Remarks Accessories: 2 Analog Robot From High strength aluminum alloy 6061-T6 2 Analog Type: body temperature Type: body temperature C Usage/Application Measuring high temperature C Usage/Application Measuring high temperature Highly accurate infrared thermometer From High temperature Should be consisted of a dial gauge with a bulb alternate to a manometer of a dial gauge with a bulb pressure instruments. 4 Sphygmomanometer Should be consisted of a dial gauge with a bulb alternate to a manometer of a dial gauge with a bulb pressure instruments.			Medicine List and Details				
Medical Oxygen Medical Oxygen Gas Cylinder 50 Litter with regulator, cylinder light Weight Cylinder, Easy to handle. ACCESSORIES: Valves, Regulators, Mask – Nasal cannula, carry bag, MATERIAL: Manufacture from High strength aluminum alloy 6061-T6 Type: body temperature Temperature Range 35-degree C to 42-degree C Usage/Application Measuring high temperature Material Glass Mighly accurate infrared thermometer for measuring temperatures from -30°C to 500°C (-22°F to 932° 22°F to 932° 22°F to 932° 2200 alternate to a manometer in calibrating pressure instruments.	NS	Equipment Name	Specification	Quantity	Unite Price	Total Price	Remarks
Valves, Regulators, Mask – Nasal cannula, carry bag, MATERIAL: Manufacture from High strength aluminum alloy 6061-T6 Type: body temperature Temperature Range 35-degree C to 42-degree C Usage/Application Measuring high temperature Material Glass Digital Thermometer Highly accurate infrared thermometer for measuring temperatures from -30°C to 500°C (- 22°F to 932° Sphygmomanometer Should be consisted of a dial gauge with a bulb and manually operated valve for the use as an alternate to a manometer in calibrating pressure instruments.	1	Medical Oxygen cylinder	Medical Oxygen Gas Cylinder 50 Litter with regulator, light Weight Cylinder, Easy to handle. ACCESSORIES:	25			
Analog Analog Type: body temperature Thermometer Thermometer Thermometer Thermometer Digital Thermometer Highly accurate infrared thermometer for measuring temperatures from -30°C to 500°C (-22°F to 932° Sphygmomanometer (Adult) Sphygmomanometer And manually operated valve for the use as an alternate to a manometer in calibrating pressure instruments.			Valves, Regulators, Mask → Nasal cannula, carry bag, MATERIAL:				
Analog Type: body temperature Thermometer Thermometer Thermometer Themperature Range 35-degree C to 42-degree C Usage/Application Measuring high temperature Material Glass Digital Thermometer Highly accurate infrared thermometer for measuring temperatures from -30°C to 500°C (- 22°F to 932° Sphygmomanometer (Adult) Sphygmomanometer (Adult) Sphygmomanometer and manually operated of a dial gauge with a bulb alternate to a manometer in calibrating pressure instruments.			Manufacture from High strength aluminum alloy 6061-T6				
Thermometer Temperature Range 35-degree C to 42-degree C Usage/Application Measuring high temperature Material Glass Digital Thermometer Highly accurate infrared thermometer for measuring temperatures from -30°C to 500°C (- 22°F to 932° Sphygmomanometer Should be consisted of a dial gauge with a bulb and manually operated valve for the use as an alternate to a manometer in calibrating pressure instruments.	2	Analog	Type: body temperature	100			
Digital Thermometer Highly accurate infrared thermometer measuring temperatures from -30°C to 500°C (-22°F to 932° Sphygmomanometer Should be consisted of a dial gauge with a bulb and manually operated valve for the use as an alternate to a manometer in calibrating pressure instruments.		Thermometer	Temperature Range 35-degree C to 42-degree C				
Digital Thermometer Highly accurate infrared thermometer for measuring temperatures from -30°C to 500°C (- 22°F to 932° Sphygmomanometer Should be consisted of a dial gauge with a bulb and manually operated valve for the use as an alternate to a manometer in calibrating pressure instruments.			Usage/Application Measuring high temperature Material Glass				
sphygmomanometer Should be consisted of a dial gauge with a bulb and manually operated valve for the use as an alternate to a manometer in calibrating pressure instruments.	ω	Digital Thermometer	Highly accurate infrared thermometer for	100			
Sphygmomanometer Should be consisted of a dial gauge with a bulb (Adult) and manually operated valve for the use as an alternate to a manometer in calibrating pressure instruments.			measuring temperatures from -30°C to 500°C (- 22°F to 932°				
Sphygmomanometer Should be consisted of a dial gauge with a bulb and manually operated valve for the use as an alternate to a manometer in calibrating pressure instruments.							
pressure instruments.	4	Sphygmomanometer (Adult)	Should be consisted of a dial gauge with a bulb and manually operated valve for the use as an alternate to a manometer in calibrating	200			
			pressure instruments.				



chest piece in zinc istant. guaranteeing uditive quality, mm, inner mm. range from 50 to 1000Hz for cardiology. 70 ange of th worker in (including length: 360) m. 2,000 2,000 2,000 2,000 70			-
eing lity. 500Hz for cardiology. Salety Bax Salety Bax	pevelop		
eing lity. n 50 to 1000Hz for cardiology. 500Hz for pneumology. salety Box	The second secon	mattress)	
istant. guaranteeing iditive quality. mm, inner mm. range from 50 to 1000Hz for cardiology. 00 Hz to 1,500Hz for pneumology. h worker in including ength: 360 n. safety Bin Safet	Size/dimension: 72X30 Inch (Length X Width)	(simple bed with	
nteeing quality, nner from 50 to 1000Hz for cardiology. o 1,500Hz for pneumology. fer in ing 360	For adult, comfortable for patients.	Bed for patients	00
nteeing quality, nner from 50 to 1000Hz for cardiology. o 1,500Hz for pneumology. fer in ing 360			
nteeing quality, nner from 50 to 1000Hz for cardiology. to 1,500Hz for pneumology. fer in ing 360			
niteeing quality, nner from 50 to 1000Hz for cardiology. to 1,500Hz for pneumology. ff salety Bax Salety Bax Salety Bax	要		
inteeing quality, inner from 50 to 1000Hz for cardiology. o 1,500Hz for pneumology. f f spley Box Spley Box			
inteeing quality, iner from 50 to 1000Hz for cardiology. to 1,500Hz for pneumology. fer in ing 360	Puncture resistance, no leakage.		
inteeing quality, nner from 50 to 1000Hz for cardiology. ter in ing 360	200		
inteeing quality, inter from 50 to 1000Hz for cardiology. to 1,500Hz for pneumology. ff agains ag	card or recycle board.		
inteeing quality, inner from 50 to 1000Hz for cardiology. to 1,500Hz for pneumology. f f a6er in ing 360	Materials: made of Kraft, water-resistant		
e in zinc eing eing ality, m 50 to 1000Hz for cardiology. 500Hz for pneumology. in	Wall thickness: 1.1-1.4mm	box	
e in zinc eing eing note in zinc seing in 50 to 1000Hz for cardiology. 500Hz for pneumology. in	Volume: 5L 2,000	Biohazard safety	7
e in zinc eing eing seing note the series of the serie	mm, width: 400 mm, height: 70 mm.		
e in zinc eing ality, m 50 to 1000Hz for cardiology. 500Hz for pneumology.	batteries); maximum dimensions: length: 360		
e in zinc eing eing note in zinc m 50 to 1000Hz for cardiology. 500Hz for pneumology.	the field. Maximum weight 4,0 kg (including		
ece in zinc iteeing quality, ner nom 50 to 1000Hz for cardiology. 1,500Hz for pneumology.	Portability: Easy to carry by a health worker in		
ece in zinc iteeing quality, ner nom 50 to 1000Hz for cardiology. 1,500Hz for pneumology.	measurement.		
cardiology.	Accuracy: ± 100 g over the entire range of		
cardiology.	Graduation: 100 g.		
			0
chest piece in zinc istant. istant, guaranteeing uditive quality, mm, inner mm. range from 50 to 1000Hz for cardiology.	Sensitivity 8.1dB in a range from 600 Hz to 1,500Hz for pneumology.		
chest piece in zinc istant. ; guaranteeing uditive quality, mm, inner	\$ensitivity from 3.2dB to 26dB in a range from 5D to 1000Hz for cardiology.		
chest piece in zinc istant. ; guaranteeing uditive quality, imm, inner	diameter 4.8mm. Tube length 560mm.		
chest piece in zinc istant. signaranteeing uditive quality,	Tube diameter: outer diameter 10mm, inner		
chest piece in zinc istant. ; guaranteeing	full transmission of sound, good auditive quality,		
chest piece in zinc	Tube impervious to outside noises, guaranteeing		
chest piece in zinc	Tube made of PVC and is crack resistant.		
chest piece in zinc	alloy.		
loi qual-use	(adult and pediatric auscultation) chest piece in zinc	ordinosco per	C
		Stathoroppe	л



T		,			7
		12	11	10	9
		Centrifuge	Microscope		Mattress and pillow for hospital examination beds
	N 300-2 m to M ← M → M → M → M → M → M → M → M → M →	User power supply 220V/100V, 50HZ Timing range 0-60 Min Rated power 40W Speed range 0-4000r/Min Capacity 20mlx12PCS (angle)	AC/DC input 220 V AC, brightfield, achromatic lens, binocular, mechanical stage; led or other illumination	Metal Stock Shelve, Adjustable, 3 bay system Size: 200X60X180¢M. Weight capacity up to 220lbs (100kg) per shelf Lightweight Easy to clean	Best Quality
		4	ω	100	70



16	15	14	13
Wheelchair	Hospital Privacy Screen	Examination bed	Autoclaye / Sterilizer
Seat Width 17-19" Type of Wheelchairs Manual Seat Height 4 feet ArmrestFixed Weight Capacity 251 to 350 Lbs. Number of Wheels 2	Size 168 cm H x 244 cm W. Frame work made of ERW tubular pipe in four folds Each piece fold 60cms wide. All four-panel fitted with two pieces of 5cm die castors Supply with spring wire and curtains. Pretreated and epoxy power coated.	Mild steel powder coated 6ft x 12 1/2 ft size Backrest operated by a lever	Electric Supply: AC 220V/50Hz KW)Power:2Cubage:24 Operating temperature:126(121°C) Optional Working Pressure(Mpa):0.142 Product size:28*21 Product size:42*42*56portable stainless steel autoclaves
ω			
3.0	200	50	20



	20	19	18	
-				17
	Refrigerator	Infrared Thermometer	Hospital trolley	Bench for hospital
evelopm	Labonatory refregerator Best Quality 250-330 Liters Capicty	Measuring body and object temperature	Size: 630*475*930MM steel structure.4 plastic steel columns equipped with 4 drawers revolving tier.	Corrosion Resistance Yes Body Material Stainless Steel No of Legs 4 Filling Material Foam No of seats 3
is a second	σ	20	70	120
1				

